

INTERCOM ENTRY SYSTEMS



MODEL 424

- Solid brass (1/4") intercom unit with **IR LEDs**
- Includes 2.97 mm color camera on adjustable bracket (35° left or right)
- Camera option: IP 2.1 Megapixel
Maximum Resolution of 1920 x 1080 @ 30fps
PoE (Power over Ethernet) and DC 12V
H.264 & Motion JPEG

- "Drawbridge" type hinges hold unit in **horizontal position for easy service**
- Back box, hardware, gasket, and instructions included
- Face plate dimensions: 8.125" x 5.125" (h w)
- Back box dimensions: 7.25" x 4.25" x 4.25" (h w d)

Options: Brushed stainless steel

HID Proximity Reader - add "P" to the part number for HID proximity reader. 2 keyfob style transmitters are included- 2.1 MP IP camera

Model 424 is available with 2 intercoms (VIO and POTS) call for details

MODEL 424-PAN2 - Includes circuit from Panasonic KX-T7775 (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board

MODEL 424-TES2 - Telephone Entry System (TES2) creates a communication link between the front door and every telephone in the house. Special telephones are not required.

MODEL 424-VIK - High performance version using **Viking** components. System uses "half-duplex" communication, allowing for high speaker and microphone volume.

OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom

MODEL 424-VIO - VoIP Intercom Module for standard SIP or **Crestron RavaSIP**. VIO features on-board IP switch for optional IP camera (one Cat 5 for audio and video).

STANDARD FINISHES: oil rubbed bronze, black powdercoat, and brushed chrome.
Allow 3 to 4 weeks for stainless steel or custom finishes.