


## INTERCOM ENTRY SYSTEM

---



### MODEL 414

- Solid brass (1/4") intercom unit
- Includes 2.97 mm color camera on adjustable bracket (35° left or right)
- Camera option: IP 2.1 Megapixel  
Maximum Resolution of 1920 x 1080 @ 30fps  
PoE (Power over Ethernet) and DC 12V  
H.264 & Motion JPEG

- "Drawbridge" type hinges hold unit in **horizontal position for easy service**
- Back box, hardware, gasket, and instructions included
- Face plate dimensions: 8.125" x 5.125" (h w)
- Back box dimensions: 7.25" x 4.25" x 4.25" (h w d)

*Options: Brushed stainless steel*

*HID Proximity Reader - add "P" to the part number for HID proximity reader. 2 keyfob style transmitters are included- 2.1 MP IP camera*

*Model 414 is available with 2 intercoms (VIO and POTS) call for details*

**MODEL 414-PAN2** -Includes circuit from Panasonic KX-T7775 (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board

**MODEL 414-TES2 - Telephone Entry System (TES2)** creates a communication link between the front door and every telephone in the house. Special telephones are not required.

**MODEL 414-VIK** - High performance version using **Viking** components. System uses "half-duplex" communication, allowing for high speaker and microphone volume.

*OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*

**MODEL 414-VIO - VoIP Intercom Module** for standard SIP or **Crestron RavaSIP**. VIO features on-board IP switch for optional IP camera (one Cat 5 for audio and video).

**STANDARD FINISHES:** oil rubbed bronze, black powdercoat, and brushed chrome.  
Allow 3 to 4 weeks for stainless steel or custom finishes.