

MODEL 1088 ADVANCED ENTRY SYSTEM



FOR NEW INSTALLATIONS OR RETRO-FIT INTO EXISTING PROJECTS

Specify intercom: VoIP or POTS

Specify keypad: Stand alone or Wiegand

Specify camera: IP or analog

Specify finish of faceplate: Black, White, Aluminum or Special

Specify finish of box: Black or White

- IR LED illumination for night viewing
- Designed to fit existing Doorking 1812 boxes
- Includes 2.97 mm color camera on adjustable bracket (35° left or right)
- Camera option: IP 2.1 Megapixel
Maximum Resolution of 1920 x 1080 @ 30fps
PoE (Power over Ethernet) and DC 12V
H.264 & Motion JPEG
- Tamper switch output can be connected to alarm system
- Auxiliary bell contact provided for automation system or camera / DVR
- Illuminated bell button, illuminated keypad
- **1088-S12** includes 1 relay. Additional relays are available
- Face plate dimensions: 6" x 9.5" (h w)
- Back box dimensions: 6.125" x 10" x 5.5" (h w d). **(Back box must be ordered separately)**

MODEL 1088-X-VIK* - High performance version using **Viking** components.

For Panasonic, use 1088-X-VIK with PAN-1 adapter

MODEL 1088-X-VIO - **VoIP Intercom Module** for standard SIP or **Crestron RavaSIP**.
VIO features on-board IP switch for optional IP camera