

INTERCOM ENTRY SYSTEMS



MODEL 120

- Solid brass (1/4") faceplate for phone systems and intercoms
- Includes 2.97 mm color camera on adjustable bracket (35° left or right)
- Camera option: IP 2.1 Megapixel
Maximum Resolution of 1920 x 1080 @ 30fps
PoE (Power over Ethernet) and DC 12V
H.264 & Motion JPEG
- Camera power supply included
- Back box, hardware, gasket, and instructions included
- Face plate dimensions: 6.4" x 4.4" (h w)
- Back box dimensions: 5.875" x 3.75" x 4" (h w d)

Options: Brushed stainless steel

2.1 MP IP camera - IP camera is not available with VIO2

MODEL 120-PAN - Compatible with **Panasonic** KSU's. Includes speaker, microphone, and circuit board.

MODEL 120-PAN2 - Includes circuit from **Panasonic KX-T7775** (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board

MODEL 120-TES2 - **Telephone Entry System (TES2)** creates a communication link between the front door and every telephone in the house. Special telephones are not required.

MODEL 120-VIK - High performance version using **Viking** components. System uses "half-duplex" communication, allowing for high speaker and microphone volume.
OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom

MODEL 120-VIK(sip) - SIP compatible unit for **Control4, Elan, or IP-PBX** phone systems. Includes Viking E-10/IP module.
OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom

MODEL 120-VIO2 **VoIP Intercom Module** for standard SIP or **Crestron RavaSIP**.