

## INTERCOM ENTRY SYSTEMS



### MODEL 200

- Solid brass (1/4") faceplate for phone systems and intercoms
- Includes 2.97 mm color camera on adjustable bracket (35° left or right)
- Camera option: IP 2.1 Megapixel  
Maximum Resolution of 1920 x 1080 @ 30fps  
PoE (Power over Ethernet) and DC 12V  
H.264 & Motion JPEG
- Camera power supply included
- Back box, hardware, gasket, and instructions included
- Includes bracket for Panasonic KX-T30865 door box
- Face plate dimensions: 7.5" x 4.4" (h w)
- Back box dimensions: 7" x 3.75" x 4.25" (h w d)

*Options: Brushed stainless steel*

*2.1 MP IP camera - IP camera is not available with VIO2*

**MODEL 200-PAN** - Compatible with **Panasonic** KSU's. Includes speaker, microphone, and circuit board.

**MODEL 200-PAN2** - Includes circuit from **Panasonic KX-T7775** (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board

**MODEL 200-TES2** - **Telephone Entry System (TES2)** creates a communication link between the front door and every telephone in the house. Special telephones are not required.

**MODEL 200-VIK** - High performance version using **Viking** components. System uses "half-duplex" communication, allowing for high speaker and microphone volume.

*OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*

**MODEL 200-VIO2** **VoIP Intercom Module** for standard SIP or **Crestron RavaSIP**.

### OTHER INTERCOM OPTIONS

Doorbell Fon, Elan, NEC, OnQ, 45 ohm

Call for details and quotations