

Tel: 714.434.6904 Fax: 800.362.0002

Web: www.eholovision.com

## INTERCOM ENTRY SYSTEMS



## **MODEL 203**

- Solid brass (1/4") faceplate for phone systems and intercoms
- Model 203 includes illuminated keypad and controller for 2 gates (16.5 volt, 40 VA power supply included)
- Includes 2.97 mm color camera on adjustable bracket (35° left or right)
- Camera option: IP <sub>2.1 Megapixel</sub>
  Maximum Resc

Maximum Resolution of 1920 x 1080 @ 30fps PoE (Power over Ethernet) and DC 12V H.264 & Motion JPEG

- Camera power supply included
- Back box, hardware, gasket, and instructions included
- Includes bracket for Panasonic KX-T30865 door box
- Face plate dimensions: 7.5" x 4.4" (h w )
- Back box dimensions: 7" x 3.75" x 4.25" (h w d)

Options: Brushed stainless steel

2.1 MP IP camera - IP camera is not available with VIO2

**MODEL 203-PAN** - Compatible with **Panasonic** KSU's. Includes speaker, microphone, and circuit board.

**MODEL 203-PAN2** -Includes circuit from **Panasonic KX-T7775** (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board

**MODEL 203-TES2** - *Telephone Entry System* (*TES2*) creates a communication link between the front door and every telephone in the house. Special telephones are not required. Includes relay for gate control.

**MODEL 203-VIK** - High performance version using **Viking** components. System uses "half-duplex" communication, allowing for high speaker and microphone volume.

OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom

**MODEL 203-VIO2** - **VoIP Intercom Module** for standard SIP or **Crestron RayaSIP**.

## OTHER INTERCOM OPTIONS

Doorbell Fon, Elan, NEC, OnQ, 45 ohm Call for details and quotations