

INTERCOM ENTRY SYSTEMS



MODEL 304

- Gate entry system in rugged steel housing (10 gauge)
- Specify **keypad** type desired: Serial ASCII output **304-A**
 Stand-alone 12 button **304-S12**
 26 Bit Wiegand output **304-W**
- **304-S12 (stand-alone keypad) does not require a controller**
- Includes 2.97 mm color camera on adjustable bracket (35° left or right)
- Camera option: IP 2.1 Megapixel
 Maximum Resolution of 1920 x 1080 @ 30fps
 PoE (Power over Ethernet) and DC 12V
 H.264 & Motion JPEG
- Includes 7.625" x 4.5" x 7.75" (h w d) steel housing
- Steel housing is metalized (rust proofing) and powdercoated black
- Includes bracket for Panasonic KX-T30865 door box
- Mounts on pipe gooseneck (optional) or in-wall

*Options: Brushed stainless steel
 2.1 MP IP camera*

MODEL 304-X-PAN - Compatible with **Panasonic KSU's**. Includes speaker, microphone, and circuit board.

MODEL 304-X-PAN2 - Includes circuit from **Panasonic KX-T7775** (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board

MODEL 304-X-TESS2 - **Telephone Entry System (TESS2)** creates a communication link between the front door and every telephone in the house. Special telephones are not required. Includes relay for gate control.

MODEL 304-X-VIK - High performance version using **Viking** components.
 OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom

MODEL 304-X-VIO - **VoIP Intercom Module** for standard SIP or **Crestron RavaSIP**. VIO features on-board IP switch for optional IP camera (one Cat 5 for audio and video).

NOTE: The "X" in the part numbers above is to specify the keypad type. See above for keypad options.

OTHER INTERCOM OPTIONS

Doorbell Fon, Elan, NEC, OnQ, 45 ohm
 Call for details and quotations