

## INTERCOM ENTRY SYSTEMS

---



### MODEL 400

- Solid brass (1/4") faceplate for phone systems and intercoms
- Specify **keypad** type desired: Serial ASCII output **400-A**  
Stand-alone 12 Button **400-S12**  
26 Bit Wiegand output **400-W**
- **400-S12 (stand-alone keypad) does not require a controller**
- Back box, hardware, gasket, and instructions included
- Face plate dimensions: 8.125" x 5.125" (h w)
- Back box dimensions: 7.25" x 4.25" x 4.25" (h w d)

*Options: Brushed stainless steel*

*HID Proximity Reader - add "P" to the part number for HID proximity reader. 2 keyfob style transmitters are included*

**MODEL 400-X-PAN2** - Includes circuit from Panasonic KX-T7775 (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board

**MODEL 400-X-TES2 - Telephone Entry System (TES2)** creates a communication link between the front door and every telephone in the house. Special telephones are not required. Includes relay for gate control.

**MODEL 400-X-VIK** - High performance version using **Viking** components. *OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*

**MODEL 400-X-VIO2 - VoIP Intercom Module** for standard SIP or **Crestron RavaSIP**.

**NOTE:** The "X" in the part numbers above is to specify the keypad type. See above for keypad options.