

INTERCOM ENTRY SYSTEMS



MODEL 401

- Solid brass (1/4") faceplate for phone systems and intercoms
- Specify **keypad** type desired: Serial ASCII output **401-A**
Stand-alone 12 button **401-S12**
26 Bit Wiegand output **401-W**
- **401-S12 (stand-alone keypad) does not require a controller**
- Includes 2.97 mm color camera on adjustable bracket (35° left or right)
- Camera option: IP 2.1 Megapixel
Maximum Resolution of 1920 x 1080 @ 30fps
PoE (Power over Ethernet) and DC 12V
H.264 & Motion JPEG
- "Drawbridge" type hinges hold unit in **horizontal position for easy service**
- **Tamper switch** output can be connected to alarm system
- Back box, hardware, gasket, and instructions included
- Face plate dimensions: 8.125" x 5.125" (h w)
- Back box dimensions: 7.25" x 4.25" x 4.25" (h w d)

Options: Brushed stainless steel

HID Proximity Reader - add "P" to the part number for HID proximity reader. 2 keyfob style transmitters are included- 2.1 MP IP camera

MODEL 401-X-PAN2 - Includes circuit from **Panasonic KX-T7775** (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board

MODEL 401-X-TES2 - **Telephone Entry System (TES2)** creates a communication link between the front door and every telephone in the house. **Special telephones are not required.** Includes relay for gate control.

MODEL 401-X-VIK - High performance version using **Viking** components. *OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*

MODEL 401-X-VIO - **VoIP Intercom Module** for standard SIP or **Crestron RavaSIP**. VIO features on-board IP switch for optional IP camera (one Cat 5 for audio and video).

NOTE: The "X" in the part numbers above is to specify the keypad type. See above for keypad options.