

## INTERCOM ENTRY SYSTEM - AXIS CAMERA

---



### **MODEL 408 ENTRY SYSTEM with AXIS NETWORK CAMERA - EURO STYLE**

- Designed for Axis M1014 network camera
- Camera is not included - it is to be supplied by dealer
- “Drawbridge” type hinges hold unit in horizontal position for easy service
- Back box, hardware, gasket, and instructions included
- Face plate dimensions: 8.125” x 5.125” (h w)
- Back box dimensions: 7.25” x 4.25” x 4.25” (h w d)

*Options: Brushed stainless steel*

*HID Proximity Reader is not available on Model 408-VIK (available with other intercoms)*

**MODEL 408-PAN2** - Includes circuit from **Panasonic KX-T7775** (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board

**MODEL 408-TES2 - Telephone Entry System (TES2)** creates a communication link between the front door and every telephone in the house. Special telephones are not required.

**MODEL 408-VIK** - High performance version using **Viking** components. See page 79 for Viking controllers.  
*OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*

**MODEL 408-VIO - VoIP Intercom Module** for standard SIP or **Crestron RavaSIP**. VIO features on-board IP switch for Axis IP camera (one Cat 5 for audio and video).