

INTERCOM ENTRY SYSTEM - AXIS CAMERA



MODEL 415

- Designed for Axis M1014 network camera
- Camera is not included - it is to be supplied by dealer
- Solid brass (1/4") faceplate for phone systems and intercoms
- Specify **keypad** type desired:

Serial ASCII output	415-A
Stand-alone 12 button	415-S12
26 Bit Wiegand output	415-W
Wiegand with built-in prox reader	415-T

- **415-S12 (stand-alone keypad) does not require a controller**

- "Drawbridge" type hinges hold unit in **horizontal position for easy service**
- **Tamper switch** output can be connected to alarm system

- Back box, hardware, gasket, and instructions included
- Face plate dimensions: 8.125" x 5.125" (h w)
- Back box dimensions: 7.25" x 4.25" x 4.25" (h w d)

Options: Brushed stainless steel

Proximity Reader is available on Model 415-T (call for details and price)

MODEL 415-X-PAN2 - Includes circuit from Panasonic KX-T7775 (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board

MODEL 415-X-TES2 - Telephone Entry System (TES2) creates a communication link between the front door and every telephone in the house. Special telephones are not required.

MODEL 415-X-VIK - High performance version using **Viking** components. System uses "half-duplex" communication, allowing for high speaker and microphone volume.

OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom - \$145

MODEL 415-VIO - VoIP Intercom Module for standard SIP or **Crestron RavaSIP**. VIO features on-board IP switch for Axis IP camera (one Cat 5 for audio and video).

NOTE: The "X" in the part numbers above is to specify the keypad type. See above for keypad options.