

Tel: 714.434.6904 Fax: 800.362.0002 Web: www.eholovision.com

## **INTERCOM ENTRY SYSTEMS**



## MODEL 421

- Solid brass (1/4") faceplate for phone systems and intercoms
- "Drawbridge" type hinges hold unit in horizontal position for easy service
- · Back box, hardware, gasket, and instructions included
- Face plate dimensions: 8.125" x 5.125" (h w)
- Back box dimensions: 7.25" x 4.25" x 4.25" (h w d)

Options: Brushed stainless steel HID Proximity Reader - add "P" to the part number for HID proximity reader. 2 keyfob style transmitters are included-

**MODEL 421-PAN2** - Includes circuit from Panasonic KX-T7775 (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board

**MODEL 421-TES2** - **Telephone Entry System** (TES2) creates a communication link between the front door and every telephone in the house. Special telephones are not required. See Page 70 for optional gate relay.

**MODEL 421-VIK** - High performance version using **Viking** components. System uses "half-duplex" communication, allowing for high speaker and microphone volume. See page 79 for Viking controllers. OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom

**MODEL 421-VIO2** - VoIP Intercom Module for standard SIP or Crestron RavaSIP.