

INTERCOM ENTRY SYSTEM with CAMERA



MODEL 505

- Includes 700 TVL color camera on adjustable bracket (35o left or right)
- Camera option: IP 2.1 Megapixel
Maximum Resolution of 1920 x 1080 @ 30fps
PoE (Power over Ethernet) and DC 12V
H.264 & Motion JPEG
- Back box, hardware, gasket, and instructions included
- Face plate dimensions: 7.5" x 3.125" (h w)
- Back box dimensions: 6.75" x 2.4" x 4" (h w d) Model 9311

• *Brushed stainless steel - (optional)*

• *2.1 MP IP camera - (optional)*

MODEL 505-PAN - Compatible with **Panasonic** KSU's. Includes speaker, microphone, and circuit board.

MODEL 505-PAN2 - Includes circuit from Panasonic KX-T7775 (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board

MODEL 505-TES2 - Telephone Entry System (TES2) creates a communication link between the front door and every telephone in the house. **Special telephones are not required.**

MODEL 505-VIK - High performance version using **Viking** components. System uses "half-duplex" communication, allowing for high speaker and microphone volume. Includes Viking E-40 module. **OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom**

MODEL 505-VIK(sip) - SIP compatible unit for **Savant** and **IP-PBX** phone systems. Includes Viking E-1600/IP module.

OTHER INTERCOM OPTIONS

MODEL 505-ELN - Compatible with **Elan**. Includes **COM2** door station model **DSF3**.

MODEL 505-OnQ - Compatible with **OnQ** Cat 5 intercom systems.