

Tel: 714.434.6904 Fax: 800.362.0002

Web: www.eholovision.com

INTERCOM ENTRY SYSTEM with BIOMETRIC



MODEL 512

- · Biometric access system with intercom
- Features ekey fingerprint keyless access systems
- Fingerprint enrollment is at door scanner for all units
- Back box, hardware, gasket, and instructions included
- Face plate dimensions: 9" x 2.75" (h w)
- Back box dimensions: 8.5" x 2" x 3.75" (h w d) Model 9310
- Brushed stainless steel (optional)

MODEL 512-X-PAN - Compatible with Panasonic KSU's. Includes speaker, microphone, and circuit board

MODEL 512-X-PAN2 -Includes circuit from Panasonic KX-T7775 (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board

MODEL 512-X-TES2 - Telephone Entry System (TES2) creates a communication link between the front door and every telephone in the house. Special telephones are not required. Includes relay for gate control.

MODEL 512-X-VIK High performance version using Viking E-40 speaker systems. OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom

MODEL 512-X-VIK(sip) - SIP compatible unit for **Control4**, **Elan**, **Savant**, **or IP-PBX phone systems**. *Includes Viking E-10/IP module*.

NOTE: The "X" in the part numbers above is to specify the biometric control system.

NOTE: The information above are for the Model 512 basic unit, which includes the faceplate, rough-in box, and communication system.

Add in the biometric access system from these choices:

Stand-Alone system - 1 relay
Stand-Alone system - 3 relay
SA3
Network System - 3 relay
Network System - Crestron version
NS C
Network System - Wiegand version
NS W

*Note: Network systems have the capacity of 40, 200, or 2000 users

NETWORK SOFTWARE: Software is required for each scanner in the network system.