

# INTERCOM ENTRY SYSTEM - PANASONIC CAMERA

---



## MODEL 513 ENTRY SYSTEM for PANASONIC NETWORK CAMERA

- Designed for WV-ST165 or other similar cameras
- Camera is not included - it is to be supplied by dealer
- “Draw-bridge” type hinges hold unit in **horizontal position for easy service**
- **Optional “aux bell contact”** available for automation system or cameras
- **Illuminated Essex piezo bell button**
  
- Face Plate dimensions 10.75” x 5.625” (h w)
- Box dimensions 10.125” x 5” x 3.50”(h w d)
- **Brushed stainless steel - (optional)**

### MODEL 513-CR - Crestron version - Includes **C2N-IIF**

**MODEL 513-PAN2** -Includes circuit from Panasonic KX-T7775 (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board

**MODEL 513-TES2 - Telephone Entry System (TES2)** creates a communication link between the front door and every telephone in the house. **Special telephones are not required.**

**MODEL 513-VIK\*** - High performance version using **Viking** components. System uses “half-duplex” communication, allowing for high speaker and microphone volume. . . **OPTION:** Upgrade to EWP (Enhanced Weather Protection) intercom. For **Panasonic**, use 513-VIK with **PAN-1** adapter

**MODEL 513-VIO - VoIP Intercom Module** for standard SIP or **Crestron RavaSIP**. VIO features on-board IP switch for Panasonic IP camera (one Cat 5 for audio and video).

## MODEL 513 OPTIONS

- **HID Proximity Reader** -
- **Oil Rubbed Bronze Finish** - brass faceplate in **ORB** finish
- **Brushed Stainless Steel** -
- **Aux bell contact** -