

INTERCOM ENTRY SYSTEM with CAMERA and KEYPAD



MODEL 518

- Solid brass (1/4") faceplate for phone systems and intercoms
- Specify **keypad** type desired: Serial ASCII output **518-A**
 Stand-alone 12 Button **518-S12**
 26 Bit Wiegand output **518-W**
- **518-S12 (stand-alone keypad) does not require a controller**
- Includes 700 TVL color camera on adjustable bracket (35o left or right)
- Camera option: IP 2.1 Megapixel
 Maximum Resolution of 1920 x 1080 @ 30fps
 PoE (Power over Ethernet) and DC 12V
 H.264 & Motion JPEG
- Face plate dimensions: 15.25" x 3" (h w)
- Back box dimensions: 14" x 2.4" x 4" (h w d) Model 9323

- *Brushed stainless steel - (optional)*
- *2.1 MP IP camera - (optional)*

MODEL 518-X-PAN - *Compatible with Panasonic KSU's. Includes speaker microphone, and circuit board.*

MODEL 518-X-PAN2 - *Includes circuit from Panasonic KX-T7775 (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board*

MODEL 518-X-TESS2 - Telephone Entry System (TESS2) *creates a communication link between the front door and every telephone in the house. **Special telephones are not required.** Includes relay for gate control.*

MODEL 518-X-VIK - *High performance version using **Viking** components. OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*

*For **Panasonic**, use 518-VIK with **PAN-1** adapter*

MODEL 518-VIK(sip) - *SIP compatible unit for **Savant** and **IP-PBX** phone systems. Includes Viking E-1600/IP module.*

NOTE: The "X" in the part numbers above is to specify the keypad type. See above for keypad options.