

BIOMETRIC ACCESS SYSTEM with KEYPAD



MODEL 525 ENTRY SYSTEM - KEYPAD AND BIOMETRIC

- Features **ekey** fingerprint keyless access systems
- Fingerprint enrollment is at door scanner for all units
- **Illuminated** keypad
- 525-CR does not include Crestron C2N-IIF

- *Brushed stainless steel - (optional)*

- Specify **keypad** type desired:

Serial ASCII output	525-A
Output for C2N-IIF <small>requires remote C2N-IIF</small>	525-CR
Stand-alone 12 button	525-S12
26 Bit Wiegand output	525-W
- Specify **biometric** access:

Stand-Alone system - 1 relay	SA1
Stand-Alone system - 3 relay	SA3
Network System - 3 relay	NS3
Network System - Crestron version	NSC
Network System - Wiegand version	NSW

- Face plate dimensions: 13.5" x 2.75" (h w)
- Back box dimensions 12.25" x 2" x 4" (h w d)

MODEL 525-X-Z

NOTE: The "X" in the part numbers above is to specify the keypad type. See above for keypad options.

NOTE: The "Z" in the part numbers above is to specify the biometric system. See above for biometric options.

NOTE: The units shown above are for the Model 525 basic unit, which includes the faceplate, and rough-in box. Add in the biometric access system from these choices:

- | | |
|--|------------|
| Stand-Alone system - 1 relay | SA1 |
| Stand-Alone system - 3 relay | SA3 |
| Network System - 3 relay | NS3 |
| Network System - Crestron version | NSC |
| Network System - Wiegand version | NSW |

***Note:** Network systems have the capacity of 40, 200, or 2000 users

NETWORK SOFTWARE: Software is required for each scanner in the network system.

STANDARD FINISHES: Model 525 is stocked only in raw brass
 Please allow about 3 weeks to have your order finished. All finishes are available