


INTERCOM ENTRY SYSTEM



MODEL 529

- Solid brass (1/4") faceplate for phone systems and intercoms
- Features HID Prox Point Plus proximity reader with 2 keyfobs
- Specify keypad type desired: Serial ASCII output 529-A
 Stand-alone 12 Button 529-S12
 26 Bit Wiegand output 529-W

- **529-S12 (stand-alone keypad) does not require a controller**

- Includes 700 TVL color camera on adjustable bracket (35o left or right)
- Camera option: IP 2.1 Megapixel
 Maximum Resolution of 1920 x 1080 @ 30fps
 PoE (Power over Ethernet) and DC 12V
 H.264 & Motion JPEG

- Face plate dimensions: 18" x 3" (h w)
- Back box dimensions: 16.75" x 2.4" x 4" (h w d) (Model 9326)

MODEL 529-X-PAN - *Compatible with Panasonic KSU's. Includes speaker microphone, and circuit board.*

MODEL 529-X-PAN2 - *Includes circuit from Panasonic KX-T7775 (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board*

MODEL 529-X-TESS2 - Telephone Entry System (TESS2) *creates a communication link between the front door and every telephone in the house. **Special telephones are not required.** Includes relay for gate control.*

MODEL 529-X-VIK - *High performance version using **Viking** components. OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*

*For **Panasonic**, use 529-VIK with **PAN-1** adapter*

MODEL 529-VIK(sip) - SIP compatible unit for **Savant** and **IP-PBX** phone systems. *Includes Viking E-1600/IP module.*