

INTERCOM ENTRY SYSTEMS



MODEL 600 ADVANCED ENTRY SYSTEM - POLE MOUNT

- **IR LED illumination** for night viewing
- Includes 2.97 mm color camera on adjustable bracket (35° left or right)
- Camera option: IP 2.1 Megapixel
Maximum Resolution of 1920 x 1080 @ 30fps
PoE (Power over Ethernet) and DC 12V
H.264 & Motion JPEG
- **Integrated 12 vDC power supply** (requires only one power supply-included)
- “Drawbrige” type hinges hold unit in **horizontal position for easy service**
- **Tamper switch** output can be connected to alarm system
- **Auxiliary bell contact** provided for automation system or camera / DVR
- **Illuminated Essex piezo bell button**
- **Illuminated keypad**
- All components are mounted to **sub-chassis** which is inserted into rough-in box at time of installation
- Specify **keypad** type desired: Serial ASCII output **600-A**
Stand-alone 12 button **600-S12**
26 Bit Wiegand output **600-W**
26 Bit Wiegand with built-in prox **600-T**
- Box dimensions 8.25” x 5.75” x 7.5” (h w d)

MODEL 600-X-VIK* - High performance version using **Viking** components.
*OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom For Panasonic, use 600-X-VIK with **PAN-1** adapter*

MODEL 600-X-VIO - **VoIP Intercom Module** for standard SIP or **Crestron RavaSIP**. VIO features on-board IP switch for optional IP camera (one Cat 5 for audio and video). **600-VIO will not fit into shallow box**

MODEL 600-X-VIK(sip) - SIP compatible unit for **IP-PBX phone systems**.
Includes Viking E-10/IP module.

Options: Brushed stainless steel

NOTE: The “X” in the part numbers above is to specify the keypad type.
See above for keypad options.

STANDARD FINISHES: Black powdercoat, anodized aluminum, and oil rubbed bronze
Allow 3 to 4 weeks for stainless steel or custom finishes.