

DUAL- INTERCOM ENTRY SYSTEM



MODEL 602 DUAL INTERCOM ENTRY SYSTEM - POLE MOUNT

MODEL 602-X-CR/VIK

- Dual intercom entry system for Crestron, VoIP, and telephone systems
- Includes 2 speakers and 2 mics for Crestron, VoIP, and telephone systems
- **For Crestron** - includes *C2N-IIF*
- **For Telephone** - includes *Viking (E-10 or W-1000)*
- **For VoIP** - includes *VIO*
- **IR LED illumination** for night viewing
- Hi Res Color Camera with **Sony ExView** chip
- **Integrated 12 vDC power supply** (requires only one power supply-included)
- “Draw bridge” type hinges hold unit in **horizontal position for easy service**
- **Tamper switch** output can be connected to alarm system
- **Illuminated Essex piezo bell button**
- **Illuminated keypad**
- All components are mounted to **sub-chassis** which is inserted into rough-in box at time of installation
- Specify **keypad** type desired:
 - Serial ASCII output **602-A**
 - Output for C2N-IIF **602-CR**
 - Stand-alone 12 button **602-S12**
 - 26 Bit Wiegand output **602-W**
- Box dimensions 8.25” x 5.75” x 7.5” (h w d)
- **IR LED illumination** for night viewing
- Includes 700 TVL color camera on adjustable bracket (35o left or right)
- Camera option: IP
 - 2.1 Megapixel
 - Maximum Resolution of 1920 x 1080 @ 30fps
 - PoE (Power over Ethernet) and DC 12V
 - H.264 & Motion JPEG

Contact our office for quotes on Dual-Intercom units