

## INTERCOM ENTRY SYSTEM



### MODEL 605 ADVANCED ENTRY SYSTEM - POLE MOUNT

- **IR LED illumination** for night viewing
- Includes 700 TVL color camera on adjustable bracket (35o left or right)
- Camera option: IP 2.1 Megapixel  
 Maximum Resolution of 1920 x 1080 @ 30fps  
 PoE (Power over Ethernet) and DC 12V  
 H.264 & Motion JPEG
- **Integrated 12 vDC power supply** (requires only one power supply-included)
- “Drawbrige” type hinges hold unit in **horizontal position for easy service**
- **Tamper switch** output can be connected to alarm system
- **Auxiliary bell contact** provided for automation system or camera / DVR
- **Illuminated Essex piezo bell button**
- **Illuminated keypad**
- All components are mounted to **sub-chassis** which is inserted into rough-in box at time of installation
- Specify **keypad** type desired: Serial ASCII output **605-A**  
 Output for C2N-IIF **605-CR**  
 Stand-alone 12 button **605-S12**  
 26 Bit Wiegand output **605-W**
- Box dimensions 8.25” x 5.75” x 7.5” (h w d)

### MODEL 605-X-CR - Crestron version - Includes **C2N-IIF**

**MODEL 605-X-VIK\*** - High performance version using **Viking** components. System uses “half-duplex” communication, allowing for high speaker and microphone volume. . *OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*  
 For **Panasonic**, use 605-X-VIK with **PAN-1** adapter

### MODEL 605-X-VIO - VoIP Intercom Module for standard SIP or Crestron RavaSIP.

**605-VIO will not fit into shallow box**

### MODEL 605 OPTIONS

- *Brushed stainless steel*
- *Oil Rubbed Bronze Finish - brass faceplate in ORB finish*
- *2.1 MP IP camera*

**NOTE:** The “X” in the part numbers above is to specify the keypad type. See above for keypad options.