

INTERCOM ENTRY SYSTEM - AXIS CAMERA



MODEL 607 ENTRY SYSTEM for AXIS NETWORK CAMERA - POLE MOUNT

- Designed for Axis M-1014 camera
 - Camera is not included - it is to be supplied by dealer
 - **Integrated 12 vDC power supply** (requires only one power supply-included)
 - “Drawbrige” type hinges hold unit in **horizontal position for easy service**
 - **Tamper switch** output can be connected to alarm system
 - **Auxiliary bell contact** provided for automation system or camera / DVR
 - **Illuminated** Essex piezo **bell button**
 - **Illuminated** keypad
 - All components are mounted to **sub-chassis** which is inserted into rough-in box at time of installation
- Specify **keypad** type desired: Serial ASCII output **607-A**
Stand-alone 12 button **607-S12**
26 Bit Wiegand output **607-W**

- Box dimensions 8.25” x 5.75” x 7.5” (h w d)

MODEL 607-X-VIK* - High performance version using **Viking** components. System uses “half-duplex” communication, allowing for high speaker and microphone volume.. *OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*
For **Panasonic**, use 607-X-VIK with **PAN-1** adapter (See Page 70 for price)

MODEL 607-X-VIO - **VoIP Intercom Module** for standard SIP or **Crestron RavaSIP**. VIO features on-board IP switch for Axis IP camera (one Cat 5 for audio and video).

607-VIO will not fit into shallow box

Options: Brushed stainless steel

NOTE: The “X” in the part numbers above is to specify the keypad type. See above for keypad options.