

## INTERCOM ENTRY SYSTEM - AXIS CAMERA



### MODEL 608 EURO-STYLE ENTRY SYSTEM for AXIS NETWORK CAMERA - POLE MOUNT

- Designed for Axis M-1014 camera
  - Camera is not included - it is to be supplied by dealer
  - **Integrated 12 vDC power supply** (requires only one power supply-included)
  - “Drawbrige” type hinges hold unit in **horizontal position for easy service**
  - **Tamper switch** output can be connected to alarm system
  - **Auxiliary bell contact** provided for automation system or camera / DVR
  - **Illuminated Essex piezo bell button**
  - **Illuminated keypad**
  - All components are mounted to **sub-chassis** which is inserted into rough-in box at time of installation
- Specify **keypad** type desired: Serial ASCII output **608-A**  
Stand-alone 12 button **608-S12**  
26 Bit Wiegand output **608-W**
  - Box dimensions 8.25” x 5.75” x 7.5” (h w d)

**MODEL 608-X-VIK\*** - *High performance version using **Viking** components. System uses “half-duplex” communication, allowing for high speaker and microphone volume.. OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*  
*For **Panasonic**, use 608-X-VIK with **PAN-1** adapter*

**MODEL 608-X-VIO** - ***VoIP Intercom Module** for standard SIP or **Crestron RavaSIP**. VIO features on-board IP switch for Axis IP camera (one Cat 5 for audio and video).*  
**608-VIO will not fit into shallow box**

*Options: **Brushed stainless steel***  
*HID Proximity Reader - add “P” to the part number for **HID***

**NOTE:** The “X” in the part numbers above is to specify the keypad type.  
See above for keypad options.