

## INTERCOM ENTRY SYSTEM



### MODEL 610 ADVANCED ENTRY SYSTEM - POLE MOUNT

- **IR LED illumination** for night viewing
- Includes 700 TVL color camera on adjustable bracket (35o left or right)
- Camera option: IP 2.1 Megapixel  
 Maximum Resolution of 1920 x 1080 @ 30fps  
 PoE (Power over Ethernet) and DC 12V  
 H.264 & Motion JPEG
- “Drawbrige” type hinges hold unit in **horizontal position for easy service**
- **Tamper switch** output can be connected to alarm system
- **Illuminated Essex piezo bell button**
- All components are mounted to **sub-chassis** which is inserted into rough-in box at time of installation
- Box dimensions 8.25” x 5.75” x 7.5” (h w d)

**MODEL 610-VIK** - High performance version using **Viking** components. System uses “half-duplex” communication, allowing for high speaker and microphone volume. . *OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*  
 For **Panasonic**, use 610-VIK with **PAN-1** adapter

**MODEL 610-VIO** - **VoIP Intercom Module** for standard SIP or **Crestron RavaSIP**.

**610-VIO will not fit into shallow box**

### MODEL 610 OPTIONS

- *Brushed stainless steel*
- *Oil Rubbed Bronze Finish - brass faceplate in ORB finish*
- *HID Proximity Reader*
- *2.1 MP IP camera*
- *Auxiliary bell contact for automation system or camera / DVR*