

DUAL- INTERCOM ENTRY SYSTEM



MODEL 702 DUAL INTERCOM ENTRY SYSTEM - FLUSH MOUNT

- Dual intercom entry system for Crestron, VoIP, and telephone systems
- Includes 2 speakers and 2 mics for Crestron, VoIP, and telephone systems
- **For Crestron** - includes **C2N-IIF**
- **For Telephone** - includes **Viking (E-10 or W-1000)**
- **For VoIP** - includes **VIO**
- **IR LED illumination** for night viewing
- Hi Res Color Camera with **Sony ExView** chip
- **Integrated 12 vDC power supply** (requires only one power supply-included)
- “Draw bridge” type hinges hold unit in **horizontal position for easy service**
- **Tamper switch** output can be connected to alarm system
- **Illuminated Essex piezo bell button**
- **Illuminated keypad**
- Specify **keypad** type desired: Serial ASCII output **702-A**
Output for C2N-IIF **702-CR**
Stand-alone 12 button **702-S12**
26 Bit Wiegand output **702-W**
- Face plate dimensions: 9.5” x 7.25” (h w)
- Back box dimensions 8.75” x 6.5” x 4.25” (h w d)
- Camera Specs: Color - Sony ExView 1/3” chip, 480 lines, 3.6 mm lens
IR pass filter (image visible in total darkness) (**standard**)

Contact our office for quotes on Dual-Intercom units