

INTERCOM ENTRY SYSTEM



MODEL 705 EURO-STYLE ENTRY SYSTEM - FLUSH MOUNT

- **IR LED illumination** for night viewing
 - Includes 700 TVL color camera on adjustable bracket (35o left or right)
 - Camera option: IP 2.1 Megapixel
 Maximum Resolution of 1920 x 1080 @ 30fps
 PoE (Power over Ethernet) and DC 12V
 H.264 & Motion JPEG
 - **Integrated 12 vDC power supply** (requires only one power supply-included)
 - “Drawbrige” type hinges hold unit in **horizontal position for easy service**
 - **Tamper switch** output can be connected to alarm system
 - **Auxiliary bell contact** provided for automation system or camera / DVR
 - **Illuminated Essex piezo bell button**
 - **Illuminated keypad**
- Specify **keypad** type desired: Serial ASCII output **705-A**
 Output for C2N-IIF **705-CR**
 Stand-alone 12 button **705-S12**
 26 Bit Wiegand output **705-W**
- Face plate dimensions: 9.5” x 7.25” (h w)
 - Back box dimensions 8.75” x 6.5” x 4.25” (h w d)

MODEL 705-X-CR - Crestron version - Includes **C2N-IIF**

MODEL 705-X-VIK* - High performance version using **Viking** components. System uses “half-duplex” communication, allowing for high speaker and microphone volume. . *OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*

*For **Panasonic**, use 705-X-VIK with **PAN-1** adapter*

MODEL 705-X-VIO - VoIP Intercom Module for standard SIP or **Crestron RavaSIP**. VIO features on-board IP switch for optional IP camera (one Cat 5 for audio and video).

MODEL 705 OPTIONS

- *Brushed stainless steel -*
- *Oil Rubbed Bronze Finish - brass faceplate in ORB finish -*
- *2.1 MP IP camera -*

NOTE: The “X” in the part numbers above is to specify the keypad type. See above for keypad options.

STANDARD FINISHES: Model 705 is stocked only in raw brass **and raw aluminum**. Please allow about 3 weeks to have your order finished. All finishes are available