

## INTERCOM ENTRY SYSTEM - AXIS CAMERA



### MODEL 707 ENTRY SYSTEM for AXIS NETWORK CAMERA - FLUSH MOUNT

- Designed for Axis M-1014 camera
  - Camera is not included - it is to be supplied by dealer
  - **Integrated 12 vDC power supply** (requires only one power supply-included)
  - “Draw bridge” type hinges hold unit in **horizontal position for easy service**
  - **Tamper switch** output can be connected to alarm system
  - **Auxiliary bell contact** provided for automation system or camera / DVR
  - **Illuminated Essex piezo bell button**
  - **Illuminated keypad**
- Specify **keypad** type desired: Serial ASCII output **707-A**  
 Output for C2N-IIF **707-CR**  
 Stand-alone 12 button **707-S12**  
 26 Bit Wiegand output **707-W**

- Face plate dimensions: 9.5” x 7.25” (h w)
- Back box dimensions 8.75” x 6.5” x 4.25” (h w d)

### MODEL 707-X-CR - Crestron version - Includes **C2N-IIF**

**MODEL 707-X-VIK\*** - High performance version using **Viking** components. System uses “half-duplex” communication, allowing for high speaker and microphone volume. . *OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*

For **Panasonic**, use 707-X-VIK with **PAN-1** adapter

**MODEL 707-X-VIO - VoIP Intercom Module** for standard SIP or **Crestron RavaSIP**. VIO features on-board IP switch for Axis IP camera (one Cat 5 for audio and video).

### MODEL 707 OPTIONS

- *Brushed stainless steel -*
- *Oil Rubbed Bronze Finish - brass faceplate in ORB finish*

**NOTE:** The “X” in the part numbers above is to specify the keypad type. See above for keypad options.