

INTERCOM ENTRY SYSTEM - AXIS CAMERA



MODEL 708 EURO-STYLE ENTRY SYSTEM for AXIS NETWORK CAMERA - FLUSH MOUNT

- Designed for Axis M-1014 camera
 - Camera is not included - it is to be supplied by dealer
 - **Integrated 12 vDC power supply** (requires only one power supply-included)
 - “Draw bridge” type hinges hold unit in **horizontal position for easy service**
 - **Tamper switch** output can be connected to alarm system
 - **Auxiliary bell contact** provided for automation system or camera / DVR
 - **Illuminated Essex piezo bell button**
 - **Illuminated keypad**
-
- Specify **keypad** type desired:

Serial ASCII output	708-A
Output for C2N-IIF	708-CR
Stand-alone 12 button	708-S12
26 Bit Wiegand output	708-W
 - Face plate dimensions: 9.5” x 7.25” (h w)
 - Back box dimensions 8.75” x 6.5” x 4.25” (h w d)

MODEL 708-X-CR - Crestron version - Includes **C2N-IIF**

MODEL 708-X-VIK* - High performance version using **Viking** components. System uses “half-duplex” communication, allowing for high speaker and microphone volume. . *OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*

For **Panasonic**, use 708-X-VIK with **PAN-1** adapter

MODEL 708-X-VIO - **VoIP Intercom Module** for standard SIP or **Crestron RavaSIP**. VIO features on-board IP switch for Axis IP camera (one Cat 5 for audio and video).

MODEL 708 OPTIONS

- *Brushed stainless steel* -
- *Oil Rubbed Bronze Finish - brass faceplate in ORB finish*

NOTE: The “X” in the part numbers above is to specify the keypad type. See above for keypad options.