

## INTERCOM ENTRY SYSTEM

---



### MODEL 709 ADVANCED ENTRY SYSTEM - FLUSH MOUNT

- **IR LED illumination** for night viewing
- Includes 709 TVL color camera on adjustable bracket (35o left or right)
- Camera option: IP 2.1 Megapixel  
Maximum Resolution of 1920 x 1080 @ 30fps  
PoE (Power over Ethernet) and DC 12V  
H.264 & Motion JPEG
- "Drawbrige" type hinges hold unit in **horizontal position for easy service**
- **Tamper switch** output can be connected to alarm system
- **Illuminated Essex piezo bell button**

- Face plate dimensions: 9.5" x 7.25" (h w)
- Back box dimensions 8.75" x 6.5" x 4.25" (h w d)

**MODEL 709-VIK** - High performance version using **Viking** components.

. *OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*  
For **Panasonic**, use 709-VIK with **PAN-1** adapter

**MODEL 709-VIO** - **VoIP Intercom Module** for standard SIP or **Crestron RavaSIP**. VIO features on-board IP switch for optional IP camera (one Cat 5 for audio and video).

### MODEL 709 OPTIONS

- *Brushed stainless steel*
- *Oil Rubbed Bronze Finish - brass faceplate in ORB finish*
- *HID Proximity Reader*
- *2.1 MP IP camera*
- *Auxiliary bell contact for automation system or camera / DVR*

**AVAILABILITY:** Model 709 is a special order product. Back boxes are kept in stock. 709 face plate is built to order. Please allow about 6-8 weeks to have your order fabricated and finished. All finishes are available.