

Tel: 714.434.6904 Fax: 800.362.0002

Web: www.eholovision.com

INTERCOM ENTRY SYSTEM - PANASONIC CAMERA



MODEL 805 EURO-STYLE ENTRY SYSTEM for PANASONIC NETWORK CAMERA - POLE MOUNT

- Designed for WV-ST165 or other similar cameras
- Camera is not included it is to be supplied by dealer
- Integrated 12 vDC power supply (requires only one power supply-included)
- "Draw bridge" hinges hold unit in horizontal position for easy service
- Tamper switch output can be connected to alarm system
- Auxiliary bell contact provided for automation system or camera / DVR
- Illuminated Essex piezo bell button
- · Illuminated keypad
- Specify keypad type desired: Serial ASCII output 805-A
 Output for C2N-IIF 805-CR
 Stand-alone 12 button 805-S12
 26 Bit Wiegand output 805-W
- Box dimensions 9.1" x 6.8" x 6.25" (h w d)

MODEL 805-X-CR - Crestron version -Includes C2N-IIF

MODEL 805-X-VIK* - High performance version using **Viking** components. System uses "half-duplex" communication, allowing for high speaker and microphone volume. . OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom

For Panasonic, use 805-X-VIK with PAN-1 adapter

MODEL 805-X-VIO - *VoIP Intercom Module* for standard SIP or *Crestron RavaSIP. VVIO* features on-board IP switch for Panasonic IP camera (one Cat 5 for audio and video)

MODEL 805 OPTIONS

- Brushed stainless steel -
- Oil Rubbed Bronze Finish brass faceplate in ORB finish

NOTE: The "X" in the part numbers above is to specify the keypad type. See above for keypad options.