

## INTERCOM ENTRY SYSTEM - PANASONIC CAMERA

---



### MODEL 909 ENTRY SYSTEM for PANASONIC NETWORK CAMERA - FLUSH MOUNT

- Designed for WV-ST165 or other similar cameras
- Camera is not included - it is to be supplied by dealer
- **Integrated 12 vDC power supply** (requires only one power supply-included)
- "Cable" type hinges hold unit in **horizontal position for easy service**
- **Tamper switch** output can be connected to alarm system
- **Auxiliary bell contact** provided for automation system or camera / DVR
- **Illuminated Essex piezo bell button**

- Face plate dimensions: 10.75" x 7.75" (h w)
- Back box dimensions 10.125" x 7.125" x 4.25" (h w d)

**MODEL 909-VIK\*** - High performance version using **Viking** components. System uses "half-duplex" communication, allowing for high speaker and microphone volume. . *OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*

For **Panasonic**, use 909-VIK with **PAN-1** adapter

**MODEL 909-VIO** - **VoIP Intercom Module** for standard SIP or **Crestron RavaSIP**. VIO features on-board IP switch for Panasonic IP camera (one Cat 5 for audio and video).

### MODEL 909 OPTIONS

- **Brushed stainless steel** -
- **Oil Rubbed Bronze Finish** - brass faceplate in **ORB** finish
- **HID Proximity Reader** -