

INTERCOM ENTRY SYSTEM



MODEL 710 EURO-STYLE ENTRY SYSTEM - FLUSH MOUNT

- **IR LED illumination** for night viewing
- Includes 700 TVL color camera on adjustable bracket (35o left or right)
- Camera option: IP 2.1 Megapixel
Maximum Resolution of 1920 x 1080 @ 30fps
PoE (Power over Ethernet) and DC 12V
H.264 & Motion JPEG
- “Drawbrige” type hinges hold unit in **horizontal position for easy service**
- **Tamper switch** output can be connected to alarm system
- **Illuminated Essex piezo bell button**

- Face plate dimensions: 9.5” x 7.25” (h w)
- Back box dimensions 8.75” x 6.5” x 4.25” (h w d)

MODEL 710-VIK* - *High performance version using **Viking** components. System uses “half-duplex” communication, allowing for high speaker and microphone volume. . OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*

*For **Panasonic**, use 710-VIK with **PAN-1** adapter*

MODEL 710-VIO - *VoIP Intercom Module for standard SIP or **Crestron RavaSIP**. VIO features on-board IP switch for optional IP camera (one Cat 5 for audio and video).*

MODEL 710 OPTIONS

- *Brushed stainless steel*
- *Oil Rubbed Bronze Finish - brass faceplate in ORB finish*
- *HID Proximity Reader*
- *2.1 MP IP camera*
- *Auxiliary bell contact for automation system or camera / DVR*

AVAILABILITY: Model 710 is a special order product. Back boxes are kept in stock. 710 face plate is built to order. Please allow about 6-8 weeks to have your order fabricated and finished. All finishes are available.