IL HOLOVISION

Tel: 714.434.6904 Fax: 800.362.0002 Web: www.eholovision.com

INTERCOM ENTRY SYSTEM with CAMERA and BIOMETRIC

MODEL 515

- · Biometric access system with intercom and camera
- Features ekey fingerprint keyless access systems
- Fingerprint enrollment is at door scanner for all unit
- Includes 700 TVL color camera on adjustable bracket (350 left or right)
- Camera option: IP 2.1 Megapixel Maximum Resolution of 1920 x 1080 @ 30fps PoE (Power over Ethernet) and DC 12V
 - H.264 & Motion JPEG
- · Back box, hardware, gasket, and instructions included
- Face plate dimensions: 9.5" x 3" (h w)
- Back box dimensions: 8.75" x 2.4" x 4" (h w d) (Model 9317)
- Brushed stainless steel (optional)
- 2.1 MP IP camera (optional)

MODEL 515-X-PAN2 - Includes circuit from Panasonic KX-T7775 (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone

MODEL 515-X-TES2 - *Telephone Entry System* (TES2) creates a communication link between the front door and every telephone in the house. Special telephones are not required.

MODEL 515-X-VIK - High performance version using **Viking** components. System uses "half-duplex" communication, allowing for high speaker and microphone volume. Includes Viking intercom module. OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom

MODEL 515-X-VIK(sip) - SIP compatible unit for **IP-PBX phone systems**. *Includes Viking E-10/IP module.*

MODEL 515-VIO2 - *VoIP Intercom Module for Crestron RavaSIP*, and **Elan. NOTE: VIO2** module must be remote-mounted.

NOTE: The "X" in the part numbers above is to specify the biometric

| NOTE: The information above are for the Model 515 basic unit, which includes the faceplate, rough-in box, |
|---|
| and communication system. |
| Add in the bigmentuic economy furner there above a |

Add in the biometric access system from these choices:

| Stand-Alone system - 1 relay | SA1 |
|-----------------------------------|------|
| Stand-Alone system - 3 relay | SA3 |
| Network System - 3 relay | NS3 |
| Network System - Crestron version | NSC |
| Network System - Wiegand version | NS W |

***Note:** Network systems have the capacity of 40, 200, or 2000 users **NETWORK SOFTWARE**: Software is required for each scanner in the network system.

AVAILABILITY: Model 515 is a special order product. Back boxes are kept in stock. 515 face plate is built to order. Please allow about 6-8 weeks to have your order fabricated and finished. All finishes are available.