

Tel: 714.434.6904 Fax: 800.362.0002

Web: www.eholovision.com

INTERCOM ENTRY SYSTEM with CAMERA, BIOMETRIC, KEYPAD and CALL BUTTON



MODEL 533

- · Biometric access system with keypad and call button (no intercom)
- · Features ekey fingerprint keyless access systems
- · Fingerprint enrollment is at door scanner for all units
- Specify keypad type desired: Serial ASCII output 533-A
 Stand-alone 12 Button 26 Bit Wiegand output 533-W
 With built-in prox reader 533-T
- 533-T features Essex T-Prox keypad with proximity reader with 2 keyfobs
- 533-S12 (stand-alone keypad) does not require a controller
- Includes 700 TVL color camera on adjustable bracket (350 left or right)
- Camera option: IP 2.1 Megapixel

Maximum Resolution of 1920 x 1080 @ 30fps PoE (Power over Ethernet) and DC 12V H.264 & Motion JPEG

- · Back box, hardware, gasket, and instructions included
- Face plate dimensions: 15.25" x 3" (h w)
- Back box dimensions: 14" x 2.4" x 4" (h w d) (Model 9323)
- Brushed stainless steel (optional)
- 2.1 MP IP camera (optional)

NOTE: The information above are for the Model 533 basic unit, which includes the faceplate, rough-in box, and camera

Add in the biometric access system from these choices:

Stand-Alone system - 1 relay
Stand-Alone system - 3 relay
SA3
Network System - 3 relay
Network System - Crestron version
NS C
Network System - Wiegand version
NS W

*Note: Network systems have the capacity of 40, 200, or 2000 users

NETWORK SOFTWARE: Software is required for each scanner in the network system.

AVAILABILITY: Model 533 is a special order product. Back boxes are kept in stock. 533 face plate is built to order. Please allow about 6-8 weeks to have your order fabricated and finished. All finishes are available.