

Tel: 714.434.6904 Fax: 800.362.0002

Web: www.eholovision.com

BIOMETRIC, KEYPAD, and CALL BUTTON



MODEL 536

- Biometric access system with call button (no intercom)
- Features **ekey** fingerprint keyless access systems
- Fingerprint enrollment is at door scanner for all units
- Specify keypad type desired: Serial ASCII output 536-A
 Stand-alone 12 Button 536-S12
 26 Bit Wiegand output 536-W
 With built-in prox reader 536-T
- 536-T features Essex T-Prox keypad with proximity reader with 2 keyfobs
- 536-S12 (stand-alone keypad) does not require a controller
- · Back box, hardware, gasket, and instructions included
- Face plate dimensions: 13.5" x 3" (h w)
- Back box dimensions: 12.25" x 2.4" x 4" (h w d) Model 9322
- Brushed stainless steel (optional)

NOTE: The units shown above are for the Model 536 basic unit, which includes the faceplate, and rough-in box. Add in the biometric access system from these choices:

Stand-Alone system - 1 relay
Stand-Alone system - 3 relay
SA3
Network System - 3 relay
Network System - Crestron version
NS C
Network System - Wiegand version
NS W

*Note: Network systems have the capacity of 40, 200, or 2000 users

NETWORK SOFTWARE: Software is required for each scanner in the network system.