


INTERCOM ENTRY SYSTEM with CAMERA and KEYPAD



MODEL 589

- Solid brass (1/4") faceplate for phone systems and intercoms
- Specify **keypad** type desired: Stand-alone 12 Button **589-S12**
26 Bit Wiegand output **589-W**
- **589-S12 (stand-alone keypad) does not require a controller**
- Includes 700 TVL color camera on adjustable bracket (35o left or right)
- Camera option: IP 2.1 Megapixel
Maximum Resolution of 1920 x 1080 @ 30fps
PoE (Power over Ethernet) and DC 12V
H.264 & Motion JPEG
- Back box, hardware, gasket, and instructions included
- Face plate dimensions: 12" x 3" (h w)
- Back box dimensions: 10.75" x 2.4" x 4" (h w d) Model 9327
- *Brushed stainless steel - (optional)*
- *2.1 MP IP camera - (optional)*

MODEL 589-X-PAN - *Compatible with Panasonic KSU's. Includes speaker, microphone, and circuit board*

MODEL 589-X-PAN2 - *Includes circuit from Panasonic KX-T7775 (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board*

MODEL 589-X-TES2 - *Telephone Entry System (TES2) creates a communication link between the front door and every telephone in the house. Special telephones are not required. Includes relay for gate control.*

MODEL 589-X-VIK *High performance version using Viking intercom module. . OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*

MODEL 589-X-VIK(sip) - SIP compatible unit for **IP-PBX** phone systems. *Includes Viking E-10/IP module.*

MODEL 589-X-VIO2 - **VoIP Intercom Module** for **Crestron RavaSIP**, and **Elan**. **NOTE:** VIO2 module must be remote-mounted.

NOTE: The "X" in the part numbers above is to specify the keypad