


Tel: 714.434.6904 Fax: 800.362.0002

Web: www.eholovision.com

## INTERCOM ENTRY SYSTEM with CAMERA, KEYPAD and PROX READER



## **MODEL 590**

- Solid brass (1/4") faceplate for phone systems and intercoms
- Specify keypad type desired: Stand-alone 12 Button 590-S12 26 Bit Wiegand output 590-W
- Features HID Prox Point Plus proximity reader with 2 keyfobs
- 590-S12 (stand-alone keypad) does not require a controller
- Includes 700 TVL color camera on adjustable bracket (350 left or right)
- Camera option: IP 2.1 Megapixel

Maximum Resolution of 1920 x 1080 @ 30fps PoE (Power over Ethernet) and DC 12V H.264 & Motion JPEG

- · Back box, hardware, gasket, and instructions included
- Face plate dimensions: 13.5" x 3.25" (h w)
- Back box dimensions: 12.25" x 2.4" x 4" (h w d) Model 9322
- Brushed stainless steel (optional)
- 2.1 MP IP camera (optional)

**MODEL 590-X-PAN** - Compatible with Panasonic KSU's. Includes speaker, microphone, and circuit board

**MODEL 590-X-PAN2** -Includes circuit from Panasonic KX-T7775 (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board

**MODEL 590-X-TES2** - Telephone Entry System (TES2) creates a communication link between the front door and every telephone in the house. Special telephones are not required. Includes relay for gate control.

**MODEL 590-X-VIK** High performance version using Viking intercom module. OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom

**MODEL 590-X-VIK(sip)** - SIP compatible unit for **IP-PBX phone systems**. *Includes Viking E-10/IP module.* 

MODEL 590-X-VIO2 - *VoIP Intercom Module for Crestron RavaSIP*, and Elan. NOTE: VIO2 module must be remote-mounted.

NOTE: The "X" in the part numbers above is to specify the keypad