

Tel: 714.434.6904 Fax: 800.362.0002

Web: www.eholovision.com

INTERCOM ENTRY SYSTEM with iOS / ANDROID APP and BIOMETRIC READER



MODEL 572

- · Speak to and see visitors on smartphone / iPad
- · Features ekey fingerprint keyless access systems
- Includes DoorBird D2100 smartphone interface
- Accommodates multiple users and multiple door stations
- · Cloud recording
- Built-in IR LEDs with light sensor
- · Doorbird module is IP 54 rated
- 2 NO NC relays
- Remote control of door/gate from smartphone
- Tamper switch output can be connected to alarm system
- · Auxiliary bell contact provided for automation system or camera / DVR
- Illuminated Essex piezo bell button

· Motion Sensor:

4D motion sensor detects moving objects from 1-10 meters (adjustable) Customize to detect objects with different directions: coming, going, both. Cloud Recording can be activated to record an image/video.

· RFID Reader:

RFID reader can trigger a notification on smartphones or trigger relay 1/2 to activate

Activate relay by touching an RFID keyfob to the built in reader RFID reader uses standard 125 KHZ and 64 bit encryption.

- Face plate dimensions: 15.125" x 4" (h w)
- Back box dimensions: 14.5" x 3.4" x 4" (h w d) (9356)

MODEL 572-X-DB - Includes DoorBird smartphone interface.

Options: Brushed stainless steel

NOTE: The information above are for the Model 572 basic unit, which includes the faceplate, rough-in box, and communication system.

Add in the biometric access system from these choices:

Stand-Alone system - 1 relay
Stand-Alone system - 3 relay
SA3
Network System - 3 relay
Network System - Crestron version
NS C
Network System - Wiegand version
NS W

*Note: Network systems have the capacity of 40, 200, or 2000 users

NETWORK SOFTWARE: Software is required for each scanner in the network system.