

Tel: 714.434.6904 Fax: 800.362.0002 Web: www.eholovision.com

INTERCOM ENTRY SYSTEM with iOS / ANDROID APP and KEYPAD

MODEL 569

- · Speak to and see visitors on smartphone / iPad
- Includes DoorBird D2100 smartphone interface
- Accommodates multiple users and multiple door stations
- Cloud recording
- Built-in IR LEDs with light sensor
- Doorbird module is IP 54 rated
- 2 NO NC relays
- Remote control of door/gate from smartphone
- · Tamper switch output can be connected to alarm system
- · Auxiliary bell contact provided for automation system or camera / DVR
- Illuminated Essex piezo bell button
- Motion Sensor:

4D motion sensor detects moving objects from 1-10 meters (adjustable) Customize to detect objects with different directions: coming, going, both. Cloud Recording can be activated to record an image/video.

RFID Reader:

RFID reader can trigger a notification on smartphones or trigger relay 1/2 to activate

Activate relay by touching an RFID keyfob to the built in reader RFID reader uses standard 125 KHZ and 64 bit encryption.

Specify keypad type desired: Serial ASCII output	569-A
Stand-alone 12 button	569-S12
26 Bit Wiegand output	569-W

- Face plate dimensions: 15.125" x 4" (h w)
- Back box dimensions: 14.5" x 3.4" x 4" (h w d) (9356)

MODEL 569-X-DB - Includes DoorBird smartphone interface.

Options: Brushed stainless steel

NOTE: The "X" in the part numbers above is to specify the keypad type. See above for keypad options.

