IN HOLOVISION

Tel: 714.434.6904 Fax: 800.362.0002 Web: www.eholovision.com

INTERCOM ENTRY SYSTEM with iOS / ANDROID APP

MODEL 732



- · Speak to and see visitors on smartphone / iPad
- Includes DoorBird D2100 smartphone interface
- · Accommodates multiple users and multiple door stations
- Cloud recording
- Built-in IR LEDs with light sensor
- Doorbird module is IP 54 rated
- 2 NO NC relays
- · Remote control of door/gate from smartphone
- Tamper switch output can be connected to alarm system
- · Auxiliary bell contact provided for automation system or camera / DVR
- Illuminated Essex piezo bell button
- Motion Sensor:

4D motion sensor detects moving objects from 1-10 meters (adjustable) Customize to detect objects with different directions: coming, going, both. Cloud Recording can be activated to record an image/video.

RFID Reader:

RFID reader can trigger a notification on smartphones or trigger relay 1/2 to activate

Activate relay by touching an RFID keyfob to the built in reader RFID reader uses standard 125 KHZ and 64 bit encryption.

Specify keypad type desired: Serial ASCII output
Stand-alone 12 button
26 Bit Wiegand output
732-A
732-S12
732-W

With built-in prox reader **732-W**

- Face plate dimensions: 9.5" x 7.25" (h w)
- Back box dimensions 8.75" x 6.5" x 4.25" (h w d)

MODEL 732-X-DB - Includes DoorBird smartphone interface.

Options: Brushed stainless steel

NOTE: The "X" in the part numbers above is to specify the keypad type. See above for keypad options.