IN HOLOVISION

0

7 8

* *

Tel: 714.434.6904 Fax: 800.362.0002 Web: www.eholovision.com

INTERCOM ENTRY SYSTEM with iOS / ANDROID APP Biometric and KEYPAD

MODEL 925

- · Speak to and see visitors on smartphone / iPad
- Includes DoorBird D2100 smartphone interface
- Accommodates multiple users and multiple door stations
- Cloud recording
- Built-in IR LEDs with light sensor
- Doorbird module is IP 54 rated
- 2 NO NC relays
- · Remote control of door/gate from smartphone
- Tamper switch output can be connected to alarm system
- · Auxiliary bell contact provided for automation system or camera / DVR
- Illuminated Essex piezo bell button
- Motion Sensor:

4D motion sensor detects moving objects from 1-10 meters (adjustable) Customize to detect objects with different directions: coming, going, both. Cloud Recording can be activated to record an image/video.

~ * 4

RFID Reader:

RFID reader can trigger a notification on smartphones or trigger relay 1/2 to activate

Activate relay by touching an RFID keyfob to the built in reader RFID reader uses standard 125 KHZ and 64 bit encryption.

 Specify keypad type desired 	Serial ASCII output Stand-alone 12 button 26 Bit Wiegand output With built-in prox reader	925-A 925-S12 925-W 925-T	
Specify biometric access:	Stand-Alone system - 1 rela	ıy	;

• Specify biometric access:	Stand-Alone system - 1 relay	SAT
	Stand-Alone system - 3 relay	SA3
	Network System - 3 relay	NS3
	Network System - Crestron version	NS C
	Network System - Wiegand version	NS W

- Face plate dimensions: 10.75" x 7.75" (h w)
- Back box dimensions 10.125" x 7.125" x 4.25" (h w d)

MODEL 925-X-DB - Includes DoorBird smartphone interface.

Options: Brushed stainless steel

NOTE: The "X" in the part numbers above is to specify the keypad type. See above for keypad options.

STANDARD FINISHES: Black powdercoat, anodized aluminum, and oil rubbed bronze Allow 3 to 4 weeks for stainless steel or custom finishes.