

Tel: 714.434.6904 Fax: 800.362.0002 Web: www.eholovision.com

## **INTERCOM ENTRY SYSTEMS**



## MODEL 410

- Solid brass (1/4") faceplate for phone systems and intercoms
- Specify keypad type desired: Serial ASCII output 410-A

Stand-alone 12 button **410-S12** 26 Bit Wiegand output **410-W** 

- 410-S12 (stand-alone keypad) does not require a controller
- "Drawbridge" type hinges hold unit in horizontal position for easy service
- Tamper switch output can be connected to alarm system
- Back box, hardware, gasket, and instructions included
- Face plate dimensions: 8.125" x 5.125" (h w)
- Back box dimensions: 7.25" x 4.25" x 4.25" (h w d)

**Options:** Brushed stainless steel

HID Proximity Reader - add "P" to the part number for HID proximity reader. 2 keyfob style transmitters are included-

**MODEL 410-X-PAN2** - Includes circuit from Panasonic KX-T7775 (amplified door station). Adjustable volume control for noisy environments. Includes Panasonic power module (mounts by KSU), speaker, microphone, and circuit board

**MODEL 410-X-TES2** - *Telephone Entry System* (TES2) creates a communication link between the front door and every telephone in the house. Special telephones are not required. Includes relay for gate control.

**MODEL 410-X-VIK** - High performance version using **Viking** components. OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom

**MODEL 410-X-VIO2** - VoIP Intercom Module for standard SIP or Crestron RavaSIP.

NOTE: The "X" in the part numbers above is to specify the keypad type. See above for keypad options.