

INTERCOM ENTRY SYSTEM



MODEL 609 ADVANCED ENTRY SYSTEM - POLE MOUNT

- **IR LED illumination** for night viewing
 - Includes 700 TVL color camera on adjustable bracket (35o left or right)
 - Camera option: IP 2.1 Megapixel
Maximum Resolution of 1920 x 1080 @ 30fps
PoE (Power over Ethernet) and DC 12V
H.264 & Motion JPEG
 - “Drawbrige” type hinges hold unit in **horizontal position for easy service**
 - **Tamper switch** output can be connected to alarm system
 - **Illuminated Essex piezo bell button**
 - All components are mounted to **sub-chassis** which is inserted into rough-in box at time of installation
- Box dimensions 8.25” x 5.75” x 7.5” (h w d)

MODEL 609-VIK - High performance version using **Viking** components. . .
OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom
*For **Panasonic**, use 609-VIK with **PAN-1** adapter*

MODEL 609-VIO - **VoIP Intercom Module** for standard SIP or
Crestron RavaSIP. VIO features on-board IP switch for optional IP camera

609-VIO will not fit into shallow box

MODEL 609 OPTIONS

- *Brushed stainless steel*
- *Oil Rubbed Bronze Finish - brass faceplate in ORB finish*
- *HID Proximity Reader*
- *2.1 MP IP camera*
- *Auxiliary bell contact for automation system or camera / DVR*