

INTERCOM ENTRY SYSTEM



MODEL 700 ADVANCED ENTRY SYSTEM - FLUSH MOUNT

- **IR LED illumination** for night viewing
- Includes 700 TVL color camera on adjustable bracket (35o left or right)
- Camera option: IP 2.1 Megapixel
Maximum Resolution of 1920 x 1080 @ 30fps
PoE (Power over Ethernet) and DC 12V
H.264 & Motion JPEG
- **Integrated 12 vDC power supply** (requires only one power supply-included)
- "Drawbrige" type hinges hold unit in **horizontal position for easy service**
- **Tamper switch** output can be connected to alarm system
- **Auxiliary bell contact** provided for automation system or camera / DVR
- **Illuminated Essex piezo bell button**
- **Illuminated keypad**
- Specify **keypad** type desired:

Serial ASCII output	700-A
Output for C2N-IIF	700-CR
Stand-alone 12 button	700-S12
26 Bit Wiegand output	700-W
- Face plate dimensions: 9.5" x 7.25" (h w)
- Back box dimensions 8.75" x 6.5" x 4.25" (h w d)

MODEL 700-X-CR - Crestron version - Includes **C2N-IIF**

MODEL 700-X-VIK* - High performance version using **Viking** components.
 . *OPTION: Upgrade to EWP (Enhanced Weather Protection) intercom*
 For **Panasonic**, use 700-X-VIK with **PAN-1** adapter

MODEL 700-X-VIO - VoIP Intercom Module for standard SIP or **Crestron RavaSIP**. VIO features on-board IP switch for optional IP camera (one Cat 5 for audio and video).

MODEL 700 OPTIONS

- *Brushed stainless steel -*
- *Oil Rubbed Bronze Finish - brass faceplate in ORB finish*
- *HID Proximity Reader -*
- *2.1 MP IP camera -*

NOTE: The "X" in the part numbers above is to specify the keypad type.
 See above for keypad options.

STANDARD FINISHES: Black powdercoat, anodized aluminum - See above for oil rubbed bronze (extra charge)
 Allow 3 to 4 weeks for stainless steel or custom finishes.